

**MATERIAL SAFETY DATA SHEET**

**Products: HWD-15 Hardwood Floor Underlayment**

**Effective: September 16, 2002**  
**Supercedes: June 4, 2001**

**Page 1 of 2**

**SECTION I**

Manufacturer's Name  
Fortifiber Corporation

Emergency Telephone No.  
508-222-3500

Address: 55 Starkey Ave., Attleboro, MA 02703

Chemical Name & Synonyms  
N/A

Trade Name & Synonyms  
None

Chemical Family  
Paper & Asphalt

Formula  
N/A

**SECTION II - HAZARDOUS INGREDIENTS**

In the solid state the material is not considered a hazardous material as defined by 21CFR 1900.1210 (OSHA Hazards Communications Law) paragraph (b) (5) (iv)

**SECTION III - PHYSICAL DATA**

Boiling Point (°F.)  
N/A

Specific Gravity (Water=1)  
> 1.0

Vapor Pressure (mmHg.)  
N/A

Percent Volatile by Volume (%)  
N/A

Vapor Density (Air=1)  
N/A

Evaporation Rate(Butyl Acetate=1)  
N/A

Solubility in Water      Negligible

Appearance & Odor: Brown to black colored paper having an asphalt odor

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

Flash Point >450°F      Method Cleveland Cup

Flammable Limits N/A      LeL N/A/VeL N/A

Extinguishing Media: Water spray, CO<sub>2</sub> fog or foam, Dry Chemical

Special Fire Fighting Procedures: The asphalt saturated paper requires that this product be treated as a fuel oil fire.

Unusual Fire and Explosion Hazards: None

